



ROTO MUT flex

COMPACT. COMPATIBLE. CLEVER.

All MUT features without a chassis

MUT
STEYR AUTOMOTIVE

ROTO MUT flex

COMPACT. COMPATIBLE. CLEVER.

MUT
STEYR AUTOMOTIVE



Key facts



body size
4.2 & 5.0 m³



compression
up to 1:5



full ROTO MUT
functionality



compatible with
tractors over 80 hp

ROTO MUT flex, the trailer-based rotary drum superstructure made in Steyr, transforms your tractor into a modern waste collection vehicle! Ideal for farmers and municipal service providers who use their tractors flexibly - whether for winter service or now also for organic waste collection.



Plug in & drive

The **ROTO MUT flex** is compatible with all common tractor types from 80 hp. A 3-pin socket in accordance with DIN 9680 is required.

The minimum requirement for the PTO shaft is 500 rpm. Standard speeds: 540E, 1,000. Recommended: 1,000.

Choose your style

You can get your **ROTO MUT flex** with body sizes of 4.2 and 5.0 m³ and in two design variants:

Styling Design

- + Cladding for additional noise reduction



Naked Design

- + exposed rotary drum reduces weight
- + conically shaped transition plates at the rear as protection



Customize your trailer like any other MUT

Like all other MUT products, our **ROTO MUT flex** comes with many additional features to make your life easier and your tours more efficient. However, none of them are compulsory, choose only those features you really need. Among the options are:

- + turn assistance system
- + driver assistance system
- + camera system for 360 all round view
- + extended lighting
- + „Clean Air“ air filter system
- + container for special tools
- + extended service and care package



scan QR code to
see it in action!





Steyr Automotive GmbH

Schönauerstraße 5

4400 Steyr

Austria

+43 7252 585-0

mut-inbox@steyr-automotive.com

steyr-automotive.com/en/mut

Please note: Errors and omissions excepted. Illustrations similar. We reserve the right to make technical changes without prior notice.

Drawings may not show the current or actual version. This document, information or advice is for guidance only and cannot be used as a basis for contractual or other obligations. No obligation, responsibility or warranty to the publisher can be inferred from it.

All information is subject to the manufacturer's tolerance specifications. A tolerance of +/- 2% must be taken into account for all weights.

