



ROTO MUT mini

SMALL. SLIM. STRONG.

Your perfect companion in narrow streets

MUT
STEYR AUTOMOTIVE

ROTO MUT mini

MUT
STEAR AUTOMOTIVE

SMALL. SLIM. STRONG



Key facts



body size
4.2-9.5 m³



compression
up to 1:5



Narrow design up
to car width



rotary drum made
of stainless steel

Our ROTO MUT rotary drum technology in combination with the compact design make our **ROTO MUT mini** your ideal companion in narrow streets, small driveways or parks - anywhere a normal vehicle cannot get to.

Maneuverable & spacious

By integrating the attachment frame into the rear section, we shorten rear overhang and optimize the axle load ratio. That creates space for various body variants and additional features to meet your specific demands.



Choose the body you need

You can get your ROTO MUT mini with body sizes between 4.2 and 9.5 m³ and in two design variants:

Styling Design

- + Cladding for additional noise reduction



Naked Design

- + exposed rotary drum
- + conically shaped transition plates at the rear as protection



Everything you need, nothing you don't want

Our ROTO MUT mini comes with many additional features to make your life easier and your tours more efficient. However, you can choose only those features, you really need:

- + turn assistance system
- + driver assistance system
- + camera system for 360 all round view
- + extended lighting
- + „Clean Air“ air filter system
- + container for special tools
- + extended service and care package



scan QR code to
see it in action!



MUT
STEYR AUTOMOTIVE

Steyr Automotive GmbH
Schönauerstraße 5
4400 Steyr
Austria

+43 7252 585-0
mut-inbox@steyr-automotive.com

steyr-automotive.com/en/mut



Please note: Errors and omissions excepted. Illustrations similar. We reserve the right to make technical changes without prior notice.

Drawings may not show the current or actual version. This document, information or advice is for guidance only and cannot be used as a basis for contractual or other obligations. No obligation, responsibility or warranty to the publisher can be inferred from it.

All information is subject to the manufacturer's tolerance specifications. A tolerance of +/- 2% must be taken into account for all weights.